lyondellbasell	These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable	
TANK TRAILER SPECIFICATION		
PRODUCT	GLYCOL ETHER	DPM
Material Characteristic and i	immediate nazard	See Product SDS
DOT SPECIFICATION	MC 307, DOT 407, (M	C 312, DOT 412 - WITH APPOVAL) STAINLESS STEEL
INSULATION	PREFERRED BUT NO	
GASKET MATERIAL		GIN TEFLON, **DOME GASKET MUST GIVE A LEAK COMPLETION OF LOADING
CONNECTIONS/FITTINGS		LESS STEEL, DUST CAPS W/SEAL PONTS, DOME LID SEALED WITH 1/8" WIRE CABLE SEAL
LIQUID CONNECTION	LOADER/INLOADER,	OF KAMLOK ADAPTER - BOTTOM REAR CENTER LOADER REQUIRE APPROVAL. NOTE: VE SPECIFIC EQUIPMENT REQUIREMENTS.
VAPOR CONNECTION	ADAPTER (GRADE L	W/BULL PLUG, 2 INCH MALE CAMLOCK, or KAMLOK EVEL VAPOR PREFERRED BUT NOT REQUIRED) **IF BULD HAVE AN ADAPTER TO ALLOW CONNECTION DT.
NITROGEN PADDING	5-7 PSIG	
TANK CLEANLINESS	IF NOT DEDICATED A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF	
STRAPPING CHART/DRIVER REQUIREMENTS	YES DRIVER REQUIREME	ENTS FOR LYONDELLBASELL SITES
HOSES	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS FIELD OF THE LYONDELLBASELL SHIPPING NOTICE.	
ADDITIONAL APPURTENANCES		LD ALWAYS NOTE CARRIER'S INSTRUCTION FOR DUIPMENT, DRIVER'S REQUIREMENT, ETC.
OTHER	TRANSWIDE CALL-O MUST ARRIVE AT PIO ALWAYS NOTIFY LYO TO POTENTIAL EXCE	NT AND MATCHING SAP SHIPPING NOTICE, OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER CKUP POINT AT SCHEDULED TIME. **DRIVER MUST ONDELL OF ANY REQUESTED LIGHT LOADING DUE EEDING LEGAL GROSS WEIGHT. PLEASE CONTACT OGISTICS WITH ANY QUESTIONS
PROHIBITED		LER WITH EMCO WHEATON FITTINGS, SITE WILL NO PETS OR ADDITIONAL PERSONNEL UNLESS

## TEAM DRIVER