

	<b>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</b>	
<b>TANK TRAILER SPECIFICATION</b>		
<b>PRODUCT</b>	<b>GLYCOL ETHER PNB</b>	
<b>Material Characteristic and immediate hazard</b>	<b>See Product SDS</b>	
<b>DOT SPECIFICATION</b>	MC 307, DOT 407, STAINLESS STEEL	
<b>HEATING/INSULATION</b>	PREFERRED BUT NOT REQUIRED	
<b>GASKET MATERIAL</b>	TEFLON ROPE, VIRGIN TEFLON, WHITE BUNA, EPDM, DOME GASKET MUST GIVE A LEAK FREE TIGHT SEAL UPON COMPLETION OF LOADING	
<b>CONNECTIONS/FITTINGS</b>	ALL MUST BE STAINLESS STEEL, DUST CAPS W/SEAL PONTS, DOME LID CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL	
<b>LIQUID CONNECTION</b>	3 "MALE CAMLOCK - BOTTOM REAR LOADER, IN-LOADER, CENTER LOADER. <b>NOTE:</b> CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS.	
<b>VAPOR CONNECTION - (ATMOSPHERIC VENT) DURING LOADING</b>	ATMOSPHERIC VENT: 3/4" to 1" BAL VALVE W/BULL PLUG, 2 INCH MALE CAMLOCK, or KAMLOK ADAPTER (GRADE LEVEL VAPOR PREFERRED BUT NOT REQUIRED) **IF 2" GLV, DRIVER SHOULD HAVE AN ADAPTER TO ALLOW CONNECTION OF 3/4" CROWS FOOT.	
<b>NITROGEN PADDING</b>	5-7 PSIG	
<b>TANK CLEANLINESS</b>	IF NOT DEDICATED A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS ARE REQUIRED FOR PROOF	
<b>STRAPPING CHART/DRIVER REQUIREMENTS</b>	YES <a href="#">DRIVER REQUIREMENTS FOR LYONDELLBASELL SITES</a>	
<b>HOSES</b>	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS FIELD OF THE LYONDELLBASELL SHIPPING NOTICE.	
<b>ADDITIONAL APPURTENANCES</b>	N/A, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTIONS FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC.	
<b>OTHER</b>	MUST HAVE CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS	
<b>PROHIBITED</b>	DO NOT EQUIP TRAILER WITH EMCO WHEATON FITTINGS, SITE WILL REJECT TRAILER. **NO PETS OR ADDITIONAL PERSONNEL UNLESS TEAM DRIVER	